

FUZEFIX HL

Screw System



- Titanium Alloy
- Cannulated
- Self Tapping/Self Drilling
- Optional Drill and Countersink
- Low Profile Head minimizes soft tissue irritation
- Torx Star Driver maximizes axial force and minimizes stripping
- Optimized Thread Pitch by diameter to maximize compression



Comprehensive

- Headless Fusion screws offered in 2.0mm, 2.5mm, 3.0mm, and 4.0mm Diameters.

Efficient

- Time saving removal system.
- Color Coded instrumentation.



A Revolutionary, Time-Saving Design.

The Innovative FuzeFix Screw Removal System offers surgeons the option to quickly remove the screw no matter the bone quality.



FUSION ORTHOPEDICS, LLC.
4135 S. Power Rd. Suite 110
Mesa, Arizona 85212 USA
(800)-403-6876
Sales@fusionorthopedics.com

Fusion
ORTHOPEDICS

FDA Cleared.
All Rights Reserved. FuzeFix is a
Trademark of Fusion Orthopedics, LLC.
D-3160-SLSX-2 Rev A

The FuzeFix Removal System is available in 3.0mm and 4.0mm screw diameters only. A surgeon must always rely on his or her own professional clinical judgment when deciding whether to use a particular product when treating a particular patient. Fusion Orthopedics does not dispense medical advice and recommends that surgeons be trained in the use of any particular product before using it in surgery. The information presented is intended to demonstrate the breadth of Fusion's product offerings. A surgeon must always refer to the package insert, product label and / or instructions for use before using any Fusion Orthopedics product.